

COLLINS TORSIONAL MECHANICAL FILTER

8- POLE DESIGN

ELECTRICAL CHARACTERISTICS	+25°C		0°C TO +60°C	
	VALUE	TOLERANCE	VALUE	TOLERANCE
CENTER FREQUENCY	455 kHz	± 0.20kHz	455 kHz	± 0.30kHz
BANDWIDTHS F3H - F3L F60H - F60L	5.50 kHz 11.00 kHz	min. max.	5.50 kHz 11.00 kHz	min. max.
PASSBAND RIPPLE	3.0 dB	max.	3.0 dB	max.
INSERTION LOSS	5.0 dB	max.	5.0 dB	max.
STOPBAND 440 kHz to F60L F60H to 470 kHz	60 dB 60 dB	min. min.	60 dB 60 dB	min. min.

NOTE: The maximum signal input voltage is 1.0 volt RMS.

ROCKWELL COLLINS
FILTER PRODUCTS
14192 Franklin Ave., CA 92780

526-8695-010

ENGINEER: D. P. Havens

FILTER TYPE: SYM

REV. LTR. --

APPROVED: F. L. Fanthorpe

FSCM NO.
2X491

DATE: 8-24-98

ENVIRONMENTAL REQUIREMENTS:

OPERATING TEMPERATURE RANGE: 0°C to +60°C

NON-OPERATING TEMPERATURE RANGE: -30°C to +85°C

VIBRATION: MIL-STD-202, Method 201, 10 G's, 10 Hz to 55 Hz

SHOCK: MIL-STD-202, Method 213B, 50 G's, 11 ms, half-sine


MECHANICAL REQUIREMENTS:

CONSTRUCTION: Sealed, Non-Hermetic

CASE STYLE: PS

MARKING: Rockwell Collins Part Number
Date Code

TEST CIRCUIT:



Note: 30 pF Includes any board stray capacitance.

ROCKWELL COLLINS
FILTER PRODUCTS
14101 MYFORD ROAD, TUSTIN, CA 92780

526-8695-010